

The Benefits to Applications of using Explicit Congestion Notification (ECN)

draft-welzl-ecn-benefits-00

Michael Welzl
University of Oslo

Gorry Fairhurst
University of Aberdeen



REDUCING INTERNET TRANSPORT LATENCY

89th IETF Meeting
London, UK
4 March 2014

What are we doing?

- ***Point of draft:***
 - document gains of ECN
 - includes less obvious gains
- ***Out of scope:***
 - To recommend a specific behavior

ECN pro's seem obvious

- “The CE codepoint of an ECN-Capable packet SHOULD only be set if the router would otherwise have dropped the packet as an indication of congestion to the end nodes.” [RFC3168]
 - The receiver gets packets instead of losing them.
 - Benefits shown in [RFC 2884], are not always biggest gain
 - In light to moderately loaded networks, number of dropped packets dropped due to congestion is small [RFC 3649]
 - ...but that's *only a part of the story*

(Note: some but not all of ECN's benefits need a different configuration than RFC 3168's “SHOULD” above)

Benefit from avoiding congestion loss

- Reduced ***Head-of-Line Blocking***
 - Relevant for transports providing in-order delivery
- TCP/SCTP: Reduced ***Probability of RTO Expiry***
 - RTO collapses cwnd, with significant bad impact; several mechanisms try to prevent this
- Some applications do not retransmit ***lost packets***
 - Typically VoIP, interactive video, real-time data
 - Need to apply loss-hiding mechanisms, with immediate effect on user-perceived quality

Benefits that require special configuration

- If ECN is configured such that routers mark packets at a lower level of congestion before they would otherwise drop packets from queue overflow:
 - Can avoid capacity overshoot; relevant e.g. in Slow Start
 - Can make congestion visible; relevant in ConEx
- If a special configuration *and* reaction are used:
 - E.g. DCTCP has shown benefits when:
 - packets are marked earlier than they would otherwise be dropped
 - an instantaneous (= not averaged) queue is used for this decision (can be achieved with a special configuration of RED)
 - Receiver precisely feeds back number of ECN marks received in an RTT

Conclusion

- Motivates people configuring host stacks and network devices to enable ECN.
- Application developers should where possible use transports that enable ECN.
- Once enabled, the benefits of ECN are provided by the transport layer and the application does not need to be rewritten to gain these benefits.

Next Steps

- Is a document of this type helpful?
- Are there *other* benefits to list?
- Do we need to explain (potential) *problems*?